

Qualified Laminated Veneer Lumber
With Low Formaldehyde Emissions

PR-E720

Revised June 15, 2017

Product: Laminated Veneer Lumber (LVL) Qualified for Low Formaldehyde Emissions

1. Basis of the product report:
 - APA Custom Product Specification E-720
 - Test method follows the principles of ISO 12460-4, Wood-Based Panels – Determination of Formaldehyde Release, Part 4: Desiccator Method, and AS/NZS 4357.4:2005, Structural Laminated Veneer Lumber, Part 4: Determination of Formaldehyde Emissions
 - ASTM D5456-13, D5456-09 and D5456-05a recognized by the 2015 IBC and IRC, 2012 IBC and IRC, and 2009 IBC, respectively
 - APA Report (see Table 2) and other qualification data
2. Product description:

LVL is made with wood veneers of various species laminated with grain parallel to the length of the member in accordance with the in-plant manufacturing standard approved by APA. LVL is available in a variety of thicknesses and sizes.
3. Formaldehyde emission level:

The G-5 rating is a formaldehyde emission level as defined in Table 1. LVL has been qualified for low formaldehyde emissions following the principles of ISO 12460-4 and AS/NZS 4357.4:2005, and the performance requirements of ASTM D 5456. LVL products meeting the formaldehyde emission level specified in Table 1 in accordance with the APA Custom Product Specification E-720 are listed in Table 2.

Table 1. Upper formaldehyde emission level for G-5 rating following the principles of ISO 12460-4 and AS/NZS 4357.4:2005^(a)

Average	0.20 mg/ℓ
Individual specimen	0.30 mg/ℓ

^(a) LVL products meeting ASTM D 5456 are not within the scope of the CARB rule or HUD regulations. The tabulated formaldehyde emission level in the G-5 standard is more stringent than the E₀ of AS/NZS 4357.4:2005 and F☆☆☆☆ of JAS Standard for Laminated Veneer Lumber, MAFF Notification 701.

4. Limitations:
 - a) LVL shall be designed and installed in accordance with the applicable provisions of the code and the recommendations provided by the manufacturers.
 - b) LVL trademarked in North America is limited to dry service conditions that result in the average moisture content of sawn lumber of less than 16 percent.
 - c) LVL products are produced by the manufacturing facilities shown in Table 2 under a quality assurance program audited by APA in accordance with the APA Custom Product Specification E-720.
 - d) This report is subject to re-examination in one year.
5. Identification:

LVL is identified by a label bearing the manufacturer's name and/or trademark, the APA assigned plant number, the product type, the APA logo, means of identifying the date of manufacture, the product report number PR-E720, and the formaldehyde emission rating G-5.

Table 2. Qualified Manufacturing Facilities for Low Formaldehyde Emission

Manufacturer	Location	Mill Number	APA Test Report
Boise Cascade Company	Lena, LA	1106	T2015P-32
Boise Cascade Company	White City, OR	1110	T2015P-32
Murphy Engineered Wood	Sutherlin, OR	1089	T2017P-22
Pacific Woodtech Corporation	Burlington, WA	1047	T2010Q-08
Roseburg Forest Products Co.	Riddle, OR	1055	T2012Q-38

APA – *The Engineered Wood Association* is an approved national standards developer accredited by American National Standards Institute (ANSI). APA publishes ANSI standards and Voluntary Product Standards for wood structural panels and engineered wood products. APA is an accredited certification body under ISO/IEC 17065 by Standards Council of Canada (SCC), an accredited inspection agency under ISO/IEC 17020 by International Code Council (ICC) International Accreditation Service (IAS), and an accredited testing organization under ISO/IEC 17025 by IAS. APA is also an approved Product Certification Agency, Testing Laboratory, Quality Assurance Entity, and Validation Entity by the State of Florida, and an approved testing laboratory by City of Los Angeles.

APA – THE ENGINEERED WOOD ASSOCIATION

HEADQUARTERS

7011 So. 19th St. • Tacoma, Washington 98466

Phone: (253) 565-6600 • Fax: (253) 565-7265 • Internet Address: www.apawood.org.

PRODUCT SUPPORT HELP DESK

(253) 620-7400 • E-mail Address: help@apawood.org

DISCLAIMER

APA Product Report® is a trademark of APA – *The Engineered Wood Association*, Tacoma, Washington. The information contained herein is based on the product evaluation in accordance with the references noted in this report. Neither APA, nor its members make any warranty, expressed or implied, or assume any legal liability or responsibility for the use, application of, and/or reference to opinions, findings, conclusions, or recommendations included in this report. Consult your local jurisdiction or design professional to assure compliance with code, construction, and performance requirements. Because APA has no control over quality of workmanship or the conditions under which engineered wood products are used, it cannot accept responsibility for product performance or designs as actually constructed.