

Duratemp[®] Exterior Siding
Roseburg Forest Products Company

PR-C302
Revised December 18, 2009

Products: Duratemp Lap and Panel Siding

Roseburg Forest Products Company, Post Office Box 1088, Roseburg, Oregon 97470

(541) 679-6767

www.rfpco.com

1. Basis of the product report:
 - 2009 and 2006 International Building Code: Section 104.11 Alternative Materials
 - 2009 and 2006 International Residential Code: Section R104.11 Alternative Materials
 - ANSI/APA Standard for Performance-Rated Engineered Wood Siding, PRP-210
 - APA Performance Standards and Qualification Policy for Structural-Use Panels, PRP-108
 - APA Reports R&D 89Q-25, T95Q-12, and T2009Q-27, and other qualification data
2. Product description:

Roseburg Duratemp exterior siding is made with a plywood base panel and a hardboard face in accordance with the specifications listed in the plant Quality Control Manual. It is available as panel siding and as lap siding, and has shiplap or square edges. Table 1 lists Roseburg Duratemp thicknesses and span ratings.
3. Design properties:

Shear wall values for Roseburg Duratemp panel siding are the same as for plywood siding as listed in Table 2306.3 of the 2009 IBC and Table 2306.4.1 of the 2006 IBC with the exception that staples are not permitted. Bracing requirements as listed in Table R602.10.2 of the 2009 IRC and Section R602.10.3 Item 3 of the 2006 IRC for wood structural panels are applicable to Roseburg Duratemp panel siding. Nailing requirements for Roseburg Duratemp panel siding are in accordance with Table 2304.9.1 of the 2009 and 2006 IBC and Table R602.3(1) of the 2009 and 2006 IRC. Roseburg Duratemp panel siding satisfies the requirements of Table R703.4 of the 2009 and 2006 IRC as exterior wall covering.
4. Product installation:

Roseburg Duratemp siding shall be installed in accordance with the recommendations provided by the manufacturer (www.rfpco.com) and APA Design/Construction Guide: *Engineered Wood Construction Guide*, Form E30 (www.apawood.org/publications). The maximum span shall be in accordance with the Span Rating shown in the trademark.
5. Fire-resistant construction:

Untreated wood structural panels have been shown to meet a Class III (or C) category for flame spread. Unless otherwise specified, fire-resistant construction shall be in accordance with APA Design/Construction Guide: *Fire-Rated Systems*, Form W305 (www.apawood.org/publications).
6. Limitations:
 - a) Roseburg Duratemp lap siding is not recognized for shear wall applications except when applied over nailable sheathing or other code recognized provisions.
 - b) Roseburg Duratemp lap or panel siding used outdoors must be finished in accordance with recommendations provided by the manufacturer (www.rfpco.com) and APA Design/Construction Guide: *Engineered Wood Construction Guide*, Form E30 (www.apawood.org/publications).
 - c) Roseburg Duratemp siding is produced at Roseburg Forest Products Company facilities in Dillard and Riddle, OR under a quality assurance program audited by APA.
 - d) This report is subject to re-examination in one year.

7. Identification:

Roseburg Duratemp siding described in this report is identified by a label bearing the manufacturer's name (Roseburg Forest Products Company) and/or trademark, the product thickness, the Span Rating, the Exposure Rating, the APA assigned plant number (480 for Dillard, OR, and 482 for Riddle, OR), the APA logo, the report number PR-C302, and a means of identifying the date of manufacture.

Table 1. Product Thicknesses and Span Ratings

Product	Thickness (in.)	Span Rating ^(a)
Lap Siding	1/2	24 o.c.
Panel Siding	3/8	16 o.c.
	13/32	16 o.c.
	15/32	16 o.c. or 24 o.c.
	1/2	16 o.c. or 24 o.c.
	19/32	16 o.c. or 24 o.c.

^(a) The Span Rating for Roseburg Duratemp siding panels in these thicknesses may vary, depending on the panel construction details and is identified in the trademark.

APA – *The Engineered Wood Association* is an accredited certification body under ISO 65 by Standards Council of Canada (SCC) and an accredited inspection agency by the International Code Council (ICC) International Accreditation Service (IAS) under ISO/IEC 17020. APA is also an accredited testing organization recognized by IAS and SCC under ISO/IEC 17025. APA is a recognized testing laboratory by Miami-Dade County, and a Product Testing Laboratory, Product Quality Assurance Entity, and Product Validation Entity by the Florida Department of Community Affairs (DCA).

**APA – THE ENGINEERED WOOD ASSOCIATION
 HEADQUARTERS**

7011 So. 19th St. • Tacoma, Washington 98466
 Phone: (253) 565-6600 • Fax: (253) 565-7265 • Internet Address: www.apawood.org

PRODUCT SUPPORT HELP DESK
 (253) 620-7400 • E-mail Address: help@apawood.org

DISCLAIMER

APA Product Report® is a trademark of APA – *The Engineered Wood Association*, Tacoma, Washington. The information contained herein is based on the product evaluation in accordance with the references noted in this report. Neither APA, nor its members make any warranty, expressed or implied, or assume any legal liability or responsibility for the use, application of, and/or reference to opinions, findings, conclusions, or recommendations included in this report. Consult your local jurisdiction or design professional to assure compliance with code, construction, and performance requirements. Because APA has no control over quality of workmanship or the conditions under which engineered wood products are used, it cannot accept responsibility of product performance or designs as actually constructed.